

SPECIFICATIONS

| Model | RH(B)-24AUL | RH(B)-120AUL | RH(B)-240AUL | |
|-----------------------------------|---|---|------------------------------------|------------------------------|
| Rated voltage | 24V DC | 120V AC (50/60Hz) | 240V AC (50/60Hz) | |
| Operating voltage | 20~30V DC | 90~110V AC | 220~260V AC | |
| Current consumption | 0.5A | 65mA | 30mA | |
| | Buzzer:50mA(RHB type only) | | | |
| Power consumption | RH | 12.0W | 6.2W | |
| | RHB | 13.2W | 6.4W | |
| Flashing cycle | 170 Flashes Per Minute | | | |
| Bulb | 24V 10W | 12V 5W | | |
| | Base:BA15S / Bulb:G18 | | | |
| Operating temperature range | -30 °C ~ +60 °C | | | |
| Mounting place | Indoor only | | | |
| Mounting direction | Upright, Updown & Sideways | | | |
| Protection rating | IP55 | | | |
| Vibration proof | Acceleration 70m/s ² Frequency range 33Hz | Acceleration 45m/s ² Frequency range 33Hz | | |
| | To be measured with an insulation measuring device of 500VDC between the terminals and the chassis. MORE THAN 1M Ω | | | |
| Dielectric voltage | Being applied between the terminals and the chassis for 1 minute. Not breaking insulation | | | |
| | 1000V AC | | 1500V AC | |
| Luminous intensity (without Dome) | 5,200cd | 3,340cd | | |
| Peak sound level (RHB type only) | 90dB (at 1m) | | | |
| Spare bulb | Without | | | |
| Mass | 0.4 kg | 0.6kg | | |
| Note | <ul style="list-style-type: none"> •This product recognized as UL standard. (Standard No.UL508, File No.E215660) •This product conform to the CE requirements and CE Marking is indicated.(RH(B)-24AUL type only) | | | |
| No. RH-120AUL-A18B-1/2 | | | | |
| PATLITE Corporation | | App. by | Chk. by | Drn. by |
| | | <i>M. Yoshida</i> 11. Jan. '05 | <i>M. Nagayama</i> 17. Jan. '05 | D. Shigematsu 7. Jan. '05 |

